



## Ridgeline<sup>®</sup> Cap Style ANSI • CSA •

ABS material – strong, yet ultra-light for seemingly weightless protection

Side clips to meet CSA standards

Low profile design – offers a low center of gravity for better balance

Available with 4- ratchet suspensions

Swinging hinge points allow you to find the most comfortable position on the back of your head

4-position harness points allows you to move the harness forward, backward, up or down – allowing for the most optimal position for ultimate comfort

Easy to grasp knob adjusts the suspension from 6½ to 8 head size

Rear padded suspension – provides additional level of comfort on the wearers' neck

Replaceable ratchet suspensions available

Replaceable sweat band - padded fabric and polyurethane foam

Vented pressure pad keeps the straps in place providing an additional level of comfort





Universal accessory slots fit cap mounted earmuffs and accessories

Ridgeline cap style hard hats pass reverse orientation, high temperature (HT) and low temperature (LT)

Non-vented hats meet Class E, G, and C safety standards for industrial head protection

Custom imprinting available

### 4-Point Ratchet | 4 Variations

-  HP44110C •• White
-  HP44130C •• Yellow
-  HP44131C •• Hi-Vis Lime
-  HP44165C •• Dark Blue

### Cap Style 4-Point Ratchet | 1 Variation

-  HP44117C •• Matte Black Graphite Pattern





HPR441 – 4-point Ratchet Replacement Suspension



HPRBANDR – Ridgeline Cap Style and Full Brim Hard Hat Sweat Band



### Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)  
Suspension: high density polyethylene (HDPE) & high impact nylon  
Sweat band: polyester fabric & polyurethane (PU) foam

### General Specifications

Weight: 358 gm  
Shell thickness: 2 - 4 mm  
Dimensions: 28 cm x 22 cm x 15.2 cm  
Suspension adjust sizing: 6.5 - 8  
Suspensions: 4-point ratchet  
Styles: vented & non-vented  
Standards: ANSI/ISEA Z89.1-2014  
Types: Type 1  
Classes: non-vented Class E, G, and C | vented Class C  
Optional features: reverse donning, hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

### Markings

Types: Type 1 offers protection to the top of the head  
Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection  
Reverse donning: accepted models the symbol molded into the brim   
HV: meets all requirements for high visibility  
LT: provides protection at low temperatures -22°F  
HT: provides protection at high temperatures 140°F  
Date code: indicated month and year when the shell was molded –  does not indicate service life

### Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use  
Never alter or modify the shell or suspension system  
Inspect the hard hat each time before use and replace if there is ANY sign of damage  
Replace hard hat after it receives a considerable impact  
Accessories such as liners have not been tested to the requirement of this standard  
Clean only with mild soap and lukewarm water  
Store hard hat in a clean, dry place that is out of direct sunlight  
Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat  
Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage