



WATCH THE  
CAPPTURE  
VIDEO

## Cappture™ and Cappture with Rubber Gasket ANSI • CE • CSA •



DIELECTRIC

Dielectric // Fits over prescription glasses // Temples extend from browbar to avoid interference with prescription frame's temples // Rubber gasket is available in select options

### Lens and Temples | 4 Variations

-  S9910ST ●●● Clear **H2X** AF
-  S9920ST ●●● Gray **H2X** AF
-  S9930ST ●● Amber **H2X** AF
-  S9960ST ●● Infinity Blue **H2X** AF

### Rubber Gasket | 2 Variations

-  S9910STMRG ●●● Clear **H2MAX** AF
-  S9920STMRG ●● Gray **H2MAX** AF



## Cappture™ and Cappture with Rubber Gasket

### General Specifications

Weight: 29.5 gm | 51.7 gm with rubber gasket

Bridge: 23.1 mm

Lens base: 2.5 curve

Lens size diagonal: 145.7 mm

Lens size vertical: 51.5 mm

Lens thickness: 1.8 mm

Overall length (lens - tip): 160 mm

Overall width (hinge - hinge): 132.5mm

Closest point between temple tips: 88 mm

### Materials

Lens: polycarbonate

Nosepiece: polycarbonate

Temple: polycarbonate

Hinge: nylon + polycarbonate

Rubber gasket: polycarbonate and thermoplastic rubber (TPR)

Part No.	Lens Marking	Temple Marking
S9910ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3
S9920ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3
S9930ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3
S9960ST	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3
S9910STMGRG	P Z87 + U6 X	P Z87 + / P c SEI CAN/CSA Z94.3
S9920STMGRG	P Z87 + U6 L2.5 X	P Z87 + / P c SEI CAN/CSA Z94.3

### Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI CAN/CSA Z94.3: CAN/CSA standard for eye and face protection devices

