








## Integra® ANSI • CE • CSA •



Adjustable temples ensure reliable performance

### Black Frame | 5 Variations

-  SB410S ••• Clear
-  SB410ST • Clear AF
-  SB420S ••• Gray
-  SB450SF ••• 5.0 IR Filter
-  SB460SF ••• 3.0 IR Filter

### Black Ratchet Frame | 1 Variation

-  SB410SR • Clear



SM4

SN4

SNWR4

SR4


### Mixed Blue Frame | 1 Variation

-  SM410S • Clear

### Blue Frame | 1 Variation

-  SN410S • Clear

### Red, White & Blue Frame | 1 Variation

-  SNWR410S • Clear

### Red Frame | 1 Variation

-  SR410S • Clear

Part No.	Lens Marking	Temple Marking
SB410S	P + U6	P Z87 + / P c SEI Z94.3
SB410ST	P + U6	P Z87 +
SB420S	P + U6 L3	P Z87 +
SB450SF	P + 5.0	P Z87 +
SB460SF	P + 3.0	P Z87 +
SB410SR	P + U6	P Z87 +
SM410S	P + U6	P Z87 +
SN410S	P + U6	P Z87 +
SNWR410S	P + U6	P Z87 +
SR410S	P + U6	P Z87 +

General Specifications
Weight: 35 gm
PD: 68 mm
Lens base: 4 curve
Lens size diagonal: 138 mm
Lens size vertical: 39 mm
Lens thickness: 2.0 mm
Overall length (lens - tip): 85 mm
Overall width (hinge - hinge): 149 mm

Materials
Lens: polycarbonate
Side shield: polycarbonate
Frame: nylon 66
Temples: nylon 66
Hinge: polycarbonate
Screw: nickel plated
Nosepiece: polycarbonate

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special purpose  
 3.0: IR3 lens  
 5.0: IR5 lens

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L3: 18% Max. Visible Light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices