



PYRAMEX
Perform At Your Peak



Ridgeline® / TruLock

TruLock™ ANSI • CE • CSA •



LOCKING
TEMPLE



DIELECTRIC

Dielectric // Lightweight
spectacle – 21 gm //
Patented temples lock
into place

Black Temples | 8 Variations

	SB9510S ●●●	Clear
	SB9510ST ●●●	Clear H2X AF
	SB9520S ●●●	Gray
	SB9520ST ●●●	Gray H2X AF
	SB9530S ●●●	Amber
	SB9556S ●●●	Multi-color Mirror
	SB9580S ●●●	I/O Mirror
	SB9580ST ●●●	I/O Mirror AF



TruLock Multi-Colors

ANSI • CE • CSA •

Sold in dozen quantity only // Comes with six assorted temple colors: red, blue, green, purple, orange and black // Multi-pack includes two of each temple color with clear lenses // Perfect for work areas where color coding is necessary

Multi-Color Temples | 2 Variations

	S9510SMP ●●●	Clear
	S9520SMP ●●●	Gray



WATCH THE VIDEO

Vimeo.com/Pyramex/TruLock

There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

ANSI Z87.1+ standards [●] | Canadian CSA Z94.3-15 & eS third-party certification [●]

For specific lens options visit our website or contact your sales representative.

TruLock™

General Specifications

Weight: 21 gm
 Bridge: 11.3 curve
 Lens base: 9.5 curve
 Lens size diagonal: 132.7mm
 Lens size vertical: 44 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 157 mm
 Overall width (hinge - hinge): 130 mm
 Closest point between temple tips: 65 mm

Materials

Lens: polycarbonate
 Temples: nylon
 Hinge: nylon

Part No.	Lens Marking	Temple Marking
SB9510S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB9510ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB9520S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB9520ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB9530S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB9556S	P Z87 + S	P Z87 + / P c SEI Z94.3
SB9580S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SB9580ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
S9510SMP	P Z87 + U6	P Z87 + / P c SEI Z94.3
S9520SMP	P Z87 + U6 L2.5	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 S: Special Purpose
 Z87: ANSI standard for eye and face protection devices
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

