

AXIS 2

SPORTS-INSPIRED



1654101 • Clear Lens



1654102 • Smoke Lens



Tilt Adjustable Arms



27 g

+ HIGH CONTOUR (10.5 BASE), DISTORTION FREE

SINGLE PIECE LENS

+ TILT ADJUSTABLE, CO-MOULDLED TEMPLE ARMS



FOR CUSTOMISED SECURE FIT PROTECTION

AGAINST DUST AND OTHER PARTICLES

bollé
SAFETY

AXIS 2

SPORTS-INSPIRED

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
AXIS 2	 Clear	1654101	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1654102	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

Ocular lens category:

- O. Range of luminous transmittance 80-100% (clear & contrast).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory
- Dental

MAIN MARKETS

- Manufacturing
- Local government and councils
- Utilities: power, gas, water and roads
- Medical and dental
- Transport
- Mining
- Construction

LENSES

- 2mm polycarbonate
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear and Smoke
- Hard coating on Contrast lens
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke and Contrast

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

14/12/2018

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY