

# UNIVERSAL



1653601 • Clear Lens



1653602 • Smoke Lens





27 g

- + 'B-FLEX' MULTI ADJUSTABLE NOSE BRIDGE
- + EXCEPTIONAL EYE COVERAGE VIA THE HIGH CONTOUR (9 BASE) SINGLE PIECE LENS
- + TILT ADJUSTMENT, CO-INJECTION MOULDED TEMPLE ARMS.

- + 'ALS' ANTI-FOG/ANTI-SCRATCH COATING

**bollé**  
SAFETY

# UNIVERSAL

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>UNIVERSAL</b>	 Gloss Jet Black / Smoke Lens	1653601	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Gloss Jet Black / Grey Polarised Lens	1653602	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

## LENS MARKING

1. The letter 'I' signifies 'Medium Impact' approval.
0. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

## OCULAR LENS CATEGORY:

0. Range of luminous transmittance 80-100% (clear).
1. Range of luminous transmittance 43 -88% (twilight).
3. Range of luminous transmittance 8 -18% (smoke).

## APPLICATIONS

- Assembly and production work
- Emergency response
- Drilling
- Rigging
- Process work
- Solar UV exposure

## MAIN MARKETS

- Manufacturing
- Construction
- Oil & gas
- Shipping
- Government
- Mining
- Medical and dental

## LENSES

2mm polycarbonate  
 9 base curve  
 'ALS' Anti-fog/anti-scratch coating on both sides of lenses: Clear and Smoke  
 100% UV 385 – Clear  
 100% UV 400 – Smoke

## CLEANING AND STORAGE

**CLEANING :** Bollé Safety recommends only using our **BOLLÉ CLEAN** Lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	No
FOAM	No
SPARE LENSES	No

## FRAME MARKING

**AS/NZS 1337.1.2010 :** Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

## ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd  
 32-40 Fairchild Street  
 Heatherton VIC 3202  
 T: 1300 138 098  
 E: safety@bolle.com.au

## NEW ZEALAND:

Bollé New Zealand Limited  
 Unit 5, 114 Sawyers Arms Road  
 Papanui, Christchurch 8052  
 T: 03 3751400  
 E: bolle@bolle.co.nz